

MA-915

Milk Analyser

Essae[®]
...for Excellence



Success Loves Speed !



Industrial Design

in Germany



Technical Specifications

Model	MA-915	
Technology	Ultrasonic Sensor	
Measuring Time	27 sec @ 30° C Milk temp	
Milk Acidity	<25° T (degree Thorn)	
Milk Measuring Temperature	10 ~ 40° C	
Milk Sample Volume	25 ml	
Display	2 x 20 Character LCD Display with Green Backlight	
Keyboard	4 Keys	
Power	AC Voltage	160 V ~ 270 V / 50 Hz
	DC Voltage	12 V ~ 14.2 V DC / 3.5 A
	Consumption	40 W
	DC Cable	DIN connector with cable length of 1.8 meter
Environment	Ambient Air Temperature	10 ~ 40° C
	Relative Humidity	30 ~ 80 %
Interface	1 x RS-232 Serial with Cable	
Cleaning	Manual & Auto	
Physical Dimensions	138 (W) x 265 (D) x 276 (H) mm	
Weight	3.1 kg	
Enclosure	ABS	

Parameter	Range	Resolution	Accuracy
Fat	0.5 ~ 15 %	0.1 %	+/- 0.1 %
SNF	3 ~ 15 %	0.1 %	+/- 0.2 %
Added Water	0 ~ 100 %	1 %	+/- 3 %
CLR	20 ~ 40	0.5	+/- 1
Lactose	1 ~ 8 %	0.1 %	+/- 0.2 %
Protein	1 ~ 6 %	0.1 %	+/- 0.2 %
Salt	0.2 ~ 1.5 %	0.1 %	+/- 0.2 %



Manual Cleaning



Bright GREEN LCD Display

Salient Value

- Faster Analysis due to Improved & Advanced Sensor Design
- Manual Cleaning for Superior Performance
- Selectable DATA format for easy interface with any Dairy software
- Cleaning & Calibration records for service with time stamp

Essae-Teraoka Pvt. Ltd.

410, 100ft Road, 4th Block,
Koramangala, Bengaluru-560 034

info@essae.com

<http://www.essae.com>

+91 80 2511 3021

1-800-425-3111

0-78488 12346



Your Essae representative

Form No. 28061-CAT-MA-915-103 R00